

Algoma Boulevard "Bioretention" Discussion June 15, 2021

Justin Gierach, P.E., Engineering Division Manager / City Engineer

UW-Oshkosh Bioretention

A Low Impact Development Proposal



- Report was put together well and was easy to follow
- Touched on some of the potential issues

City of Oshkosh and Bioretention


Safety Building/City Hall




City of Oshkosh and Bioretention

Seniors Center








West 9th Avenue Reconstruction Rural to urban conversion PROPOSED WEST 9TH AVENUE PAVEMENT CROSS SECTION **OPTION 3- PARKING BOTH SIDES** 80' RIGHT OF WAY 16' 48' FACE TO FACE CONCRETE PAV'T 10.5 8' 10.5' 111 5' PARKING LANE BIKE LANE TRAVEL LANE BIKE LANE PARKING LANE WALK GRASS TRAVEL LANE GRASS WALK _0.5' 的人名英格兰 医皮肤 医二氏性 医多种性 医多种性 医克里特氏 医二氏性 医二氏性 医二氏性 医二氏性


West 9th Avenue Reconstruction


Rural to urban conversion





Table 2. Water quality BWPs Canadared Med 9" Are see Renewins the Stans Water Services City of Delicant, WI		
DVP+	BMP Harm	Concept Description
1	Earth Residue	Install catchdooks with large with the atom sower splane. Once be of both per in conjunction within BMPs.
2	Proportion, Score Varie Filtra- tion Devices	head physically someway filter or token
1	Qualifican Form Sandhisson Estatement Shada	Costs over it is second activing west side of Qualifian Fallin Schalles with the Divertime of the work the More III - Posts and the souls.
4	Denne Horstonica or Sooks	this restricts be delenge and cross grown and on blooder its course with the case of the total New Years.
	Wilde mass Physics Wes Commission Parast	Construct a very describe basis within version feet on the north didn of West \$100, must then our one by boundaries of Wilderman Physics.
. E	Farmachile Programmet	Intil preside power with a princil to motive
7	Mincy Hospital Hord: Well De- tendion Easts	Direct sport to participate and expenses the great address Quid Fan ment Substitute and into an integration (Substitute and integration (Substitute and Substitute and Subs
	Photocart Creek Drive Dry Determine tion Davids Detroits & Diversion	If yet augitte work in Photosis Cardi Dive to misting dyvincerion trade. Convert dyvincerio basin to ver catantice basin.
(1)	Subarries inflament Transp	All culcis busins install a performed price out of the busis of the cutch busis into undoes an expense and influence gallery.
w	School Sanchiller	At tasks begins the fall is perfected place on of the back of the casts backs into a cool fiber ress. On text such a booken of the record real major of the bornability states sever that can of indicate through the instance of the fiber.
11	(wasy kw	Install solutor Rev (progricus) sturn water equipper claration (registron in exchanges).
12	ShetGerri	Utilize the estaling Ony smeet cleaning operations for the new artern cross section.














Algoma Boulevard Reconstruction

- Other challenges to install in the Right of Way (ROW)
 - Other existing utilities
 - Sanitary Laterals (can be 5'-10' deep)
 - Water Laterals (typically ~6.5′ deep)
 - Storm Laterals (typically 3'-6' deep)
 - · UWO Facilities
 - Chilled Water Lines (depth can vary and is unknown)
 - Steam ducts/tunnels (depth can vary and is unknown)
 - Private Utility Companies Relocation (may be compensatory)
 - Telecommunications (typically 2'-4' deep)
 - AT&T
 - · Charter
 - NTD
 - WPS (Electric and Gas)
 - · Power Poles
 - City Electric Facilities (typically 2'-3' deep)
 - · Street lighting
 - Fiber

Algoma Boulevard Reconstruction

- Maintenance Requirements
 - It is stated several times within the report that Bioretention facilities are "self-reliant", "self-sustaining", "less maintenance" etc...
 - "Less mowing for the university and less maintenance"
 - "Once established, the plants will continue to grow in the bioswale and not need additional attention"

Algoma Boulevard Reconstruction

Bioretention For Infiltration (1004)

Wisconsin Department of Natural Resources Technical Standard

Table 6. Typical Maintenance Activities for Bioretention Areas			
ACTIVITY	FREQUENCY		
Water Plants	As necessary during first growing season		
Water as necessary during dry periods	As needed after first growing season		
Re-mulch void areas	As needed		
Treat diseased trees and shrubs	As needed		
Inspect soil and repair eroded areas	Monthly		
Remove liter and debris	Monthly		
Add additional mulch	Once per year		

Place the infiltration device in a site that is visible to encourage routine up-keep and maintenance. Choose a site that provides ample room for maintenance access to all parts of the device. Consider traffic visibility and other safety issues when siting the infiltration device.


Bioretention devices are not suitable for controlling construction site erosion. These devices will not treat chlorides, and will be damaged by heavy loading of salt-based deicers.

D. Snow shall not be dumped directly onto the conditioned planting bed.

400 Block North Main Street Parking Lot









Algoma Boulevard Reconstruction

- Overall, the City looks at and uses Best Management Practices (BMP's) wherever practical/required.
- NR 151 does not require BMP's for TSS reductions on this type of a project.
- Initial installation costs were never planned for.
- Maintenance costs would be an ongoing (forever) issue.
- As of today, DPW has not found a good spot to use Biofilters/Bioretention on Street Reconstruction projects.
 - Existing utilities
 - Maintenance
 - Soil types
- Specifically this case, I can see an argument on both sides for pedestrian safety.
 - Curranty there is a fence stopping pedestrians from "jaywalking"
 - · Bioretention may not "stop" the jaywalking

Algoma Boulevard "Bioretention" Discussion June 15, 2021

Questions:

Justin Gierach, P.E., Engineering Division Manager / City Engineer

(920) 236-5065

www.ci.oshkosh.wi.us

06/15/2021

Algoria Biofilters Discussion

